

Y Splitter M8-male to M12-female

Description:

Used for sensors, I/O connector connecting. Standard threaded connection.
 Straight series and angled series are available. 3, 4-core are optional.
 Customized cable lengths. Degree of protection IP67.



Features:

- PVC, PUR are optional
- A-coded interface
- Optional LED indicator

* All technical information about the raw cable for connectors, please refer to the "cable" section (P513).

Type Code

Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
PVC	Straight to 2 straight	ECS-E2CO12.3-2/2	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 angled	ECS-E2CBO12.3-2/2	4-3/3	4A/30V	2m	0.25mm ²
PUR	Straight to 2 straight	ECS-E2CO12.3-2/2/P	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 angled	ECS-E2CBO12.3-2/2/P	4-3/3	4A/30V	2m	0.25mm ²

Selection Instructions

ECS-E2CO12.3-2/2/P

① ②

- Attn :
- ①: Customized cable lengths are available.
 - ②: Cable jacket or function can be customized according to the requirements.

Additional Information

Cable Length	Wiring Diagram
	<p>Standard</p>

Y Splitter M8-male to M12-female

Description:

Used for sensors, I/O connector connecting. Standard threaded connection. Advanced design idea of female terminal to male terminal. Straight series and angled series are available. 3, 4-core are optional. Customized cable lengths. Degree of protection IP67.



Features:

- PVC and PUR cable are optional
- A-coded interface
- LED indicator

* All technical information about the raw cable for connectors, please refer to the "cable" section (P513).

Type Code

Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section	
PVC	Straight to 2 straight	PNP	ECS-E2CO12.3-2/2/L	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 angled	PNP	ECS-E2CBO12.3-2/2/L	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 straight	NPN	ECS-E2CO12.3-2/2/LN	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 angled	NPN	ECS-E2CBO12.3-2/2/LN	4-3/3	4A/30V	2m	0.25mm ²
PUR	Straight to 2 straight	PNP	ECS-E2CO12.3-2/2/L/P	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 angled	PNP	ECS-E2CBO12.3-2/2/L/P	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 straight	NPN	ECS-E2CO12.3-2/2/LN/P	4-3/3	4A/30V	2m	0.25mm ²
	Straight to 2 angled	NPN	ECS-E2CBO12.3-2/2/LN/P	4-3/3	4A/30V	2m	0.25mm ²

Selection Instructions

ECS-E2CO12.3-2/2/L/P

① ②

- Attn :
- ①: Customized cable lengths are available.
 - ②: Cable jacket or function can be customized according to the requirements.

Additional Information

Cable Length	Wiring Diagram	Product with LED	
	<p>Standard</p>	<p>PNP 3-core</p>	<p>NPN 3-core</p>